

SPECIFICATION
ALUMINIUM HOUSING
OPAL ACRYLIC DIFFUSER
ALUMINIUM LOUVRE



FINISH
ANODISED ALUMINIUM
ANODISED WHITE

COMMODORE

A surface-mounted or pendant T5 luminaire with louvre or opal diffuser. Optional downlight elements.



REFERENCE	LAMPS	LENGTH (mm)
SINGLE LENGTH STANDARD MODULE WITH LOUVRE		
CMD 133 149	1 x 49 watt T5	1490
CMD 133 154	1 x 54 watt T5	1190
CMD 133 249	2 x 49 watt T5	2970
CMD 133 254	2 x 54 watt T5	2370

REFERENCE	LAMPS	LENGTH (mm)
SINGLE LENGTH STANDARD MODULE WITH OPAL DIFFUSER		
CMD 134 149	1 x 49 watt T5	1490
CMD 134 154	1 x 54 watt T5	1190
CMD 134 249	2 x 49 watt T5	2875
CMD 134 254	2 x 54 watt T5	2275

REFERENCE	LAMPS	LENGTH (mm)
T5 MODULE PLUS MR16 DOWNLIGHTS		
CMD 135 1492	1 x 49 watt T5 + 2 x MR16	1800
CMD 135 1542	1 x 54 watt T5 + 2 x MR16	1500
CMD 135 2493	2 x 49 watt T5 + 3 x MR16	3400
CMD 135 2543	2 x 54 watt T5 + 3 x MR16	2800

ADD SUFFIX /LL for lamella louvre option
/OD for opal acrylic diffuser
/EM for integral emergency version
/AL for anodised aluminium finish
/AW for white anodised aluminium finish



DIMENSIONS

MOUNTING
WIRE SUSPENSION

LAMPS
T5 + / MR16

DISTRIBUTION

PENDANT
COMMODORE

DETAIL

IP RATING **_20**
WEIGHT [KG] **_4.3/METRE**

CE