



# Specification Book

INCORPORATING:


ENDURANCE

ELEMENTS

ONE2SEE SIGNS

RETRO-FIT

MADE2SPEC



# INTRODUCTION

---

This publication provides  
quick reference  
specification details for  
the following Aether  
Lighting ranges

## ENDURANCE

---

VANDAL & WEATHER RESISTANT LIGHTING

## ELEMENTS

---

AFFORDABLE AND RELIABLE INTERIOR LIGHTING

## ONE2SEE SIGNS

---

SIGNS, TRAYS & BOLLARDS FOR STREET LIGHTING

## RETRO-FIT


---

HIGH QUALITY, EFFICIENT AND EASY TO FIT RETRO-FIT GEAR TRAYS FOR COMMERCIAL PREMISES

## MADE2SPEC

---

BESPOKE LIGHT FITTINGS TO YOUR DESIGN SPECIFICATIONS



# CONTENTS/INDEX

## BY RANGE (ALPHABETICAL):

Elements	30
Endurance	06
Made2Spec	60
One2See	48
Retro-fit	56

Please note that whilst all details stated in this brochure are correct at the time of going to print, in line with our ongoing policy of continual improvement or unforeseen supplier shortages we reserve the right to change any product (which includes, but is not limited to, aesthetic appearance, dimensions, lumen outputs, load wattages, stated drivers) at any time.

## BY PRODUCT (ALPHABETICAL):

Arcola	25	Kalix	13
Arcola 195	39	Kalix AL	13
Arcola 85	38	Liner	35
Arcola AL	25	Mani	52
Arena	21	Metro	51
Batt	47	Ring	36
Bella	26	Rotunda	40
Borough	54	Saya	52
Chin	52	Shallow	43
Citadel	22	Shallow Mini	42
Citadel45	23	Sid	52
City	55	Simon	53
Cosmo	50	SQ	10
Covello	12	SQ45	11
Disc	37	Tabor	16
Emma	52	Tabor45	17
Forum	14	Tabor Compact	18
Forum45	15	Tabor Square	19
Glance	41	Uprail	24
Grid	44	Vap	46
Grid Wing	45	Varberg	20
Isla	27	Wash	34





## Vandal & Weather Resistant Lighting

URBAN REGENERATION

SOCIAL HOUSING

LOCAL AUTHORITY

TRANSPORT

SECURE ESTABLISHMENTS



**SQ**  
Page 10



**SQ45**  
Page 11



**COVELLO**  
Page 12



**KALIX**  
Page 13



**FORUM**  
Page 14



**FORUM45**  
Page 15



**TABOR**  
Page 16



**TABOR45**  
Page 17



**TABOR COMPACT**  
Page 18



**TABOR SQUARE**  
Page 19





**VARBERG**  
Page 20



**ARENA**  
Page 21



**CITADEL**  
Page 22




**CITADEL45**  
Page 23



**UPRAIL**  
Page 24



**ARCOLA**  
Page 25



**BELLA**  
Page 26



**ISLA**  
Page 27

# SQ


## SQUARE LED BULKHEAD

Square bulkhead developed with LED at the forefront of its design, combining high performance, strength and durability.

Body in zinc coated steel.

3mm opal polycarbonate diffuser secured by anti-tamper fixings.

1420,1950 and 2200lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".



### PRODUCT CODE

SQ/1420

SQ/1950

SQ/2200

### LUMENS

1420

1950

2200

### LOAD

8W

10W

12W

### CCT:

4000K

### Finish:


Painted Textured Black

### IP:

65

### IK:

14



## SQ45

### ANGLED LED BULKHEAD

Wall mount angled bulkhead developed with LED at the forefront of its design, combining high performance, strength and durability.

Body in zinc coated steel.

3mm opal polycarbonate diffuser secured by anti-tamper fixings.

1420,1950 and 2200lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Textured Black
<b>IP:</b>	65
<b>IK:</b>	14

PRODUCT CODE	LUMENS	LOAD
SQ45/1420	1420	8W
SQ45/1950	1950	10W
SQ45/2200	2200	12W

Other colours and technical modifications available, see page 29 for details.


# COVELLO

## CIRCULAR LED ARCHITECTURAL BULKHEAD

Circular architectural bulkhead with aesthetics and LED performance at the forefront of its design. Great lines, high performance, strength and durability make Covello the perfect choice. Die cast aluminium body & frame finished matt black.

3mm opal injection moulded polycarbonate diffuser secured by anti-tamper fixings.

1420,1950 and 2200lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".



### PRODUCT CODE

COV/1420

COV/1950

COV/2200

### LUMENS

1420

1950

2200

### LOAD

8W

10W

12W

### CCT:

4000K

### Finish:


Painted Matt Black

### IP:

65

### IK:

18



**CCT:** 4000K  
**Finish:** Painted RAL9010  
**IP:** 65  
**IK:** 20

PRODUCT CODE	LUMENS	LOAD
KAL/1420	1420	8W
KAL/1950	1950	10W
KAL/2200	2200	12W
KAL/3000	3000	17W

## KALIX

### EXCEPTIONALLY STRONG CIRCULAR LED FITTING

Round bulkhead developed with LED at the forefront of its design.

Steel spun body and diffuser frame. Rear fixing holes.

3mm opal polycarbonate diffuser secured by anti-tamper fixings.

Anti-ligature version also available.

1420,1950 and 2200lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".



Other colours and technical modifications available, see page 29 for details.




# FORUM

## STRONG & SLIM LED LUMINAIRE

Linear LED fitting with a contemporary design; slim, efficient & strong.  
Body in zinc coated steel.


3mm opal polycarbonate diffuser  
secured by anti-tamper fixings.

4500, 4900 & 5800lm are supplied set  
to ordered level but version for on-site  
switchable output is available - add  
suffix "ADJ".



PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
FOR/4/4500	4500	1200mm	28W
FOR/4/4900	4900	1200mm	30W
FOR/4/5800	5800	1200mm	35W

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Textured Black
<b>IP:</b>	65
<b>IK:</b>	14



## FORUM45

### STRONG & SLIM ANGLED LED LUMINAIRE

Angled linear LED fitting with a contemporary design; slim, efficient & strong.

Body in zinc coated steel.

3mm opal polycarbonate diffuser secured by anti-tamper fixings.

4500, 4900 & 5800lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Textured Black
<b>IP:</b>	65
<b>IK:</b>	14

PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
FOR45/4/4500	4500	1200mm	28W
FOR45/4/4900	4900	1200mm	30W
FOR45/4/5800	5800	1200mm	35W

Other colours and technical modifications available, see page 29 for details.

# TABOR

## STRONG & DURABLE LED LINEAR LUMINAIRE

Super-slim 'tough brother' of the Forum, designed for installations where severe or prolonged attack may occur. Body in zinc coated steel.


3mm opal polycarbonate diffuser secured by anti-tamper fixings.

620mm version is provided utilising a flat opal polycarbonate panel.

2250, 2450 & 2900lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".


4500, 4900 & 5800lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".

Other colours and technical modifications available, see page 29 for details.  
Anti-ligature as standard when ceiling mounted.



PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
TAB/2/2250	2250	620mm	14W
TAB/2/2450	2450	620mm	15W
TAB/2/2900	2900	620mm	18W
TAB/4/4500	4500	1200mm	28W
TAB/4/4900	4900	1200mm	30W
TAB/4/5800	5800	1200mm	35W

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Textured Black
<b>IP:</b>	65
<b>IK:</b>	18



# TABOR45

## STRONG & SLIM ANGLED LED LUMINAIRE

The 'tough brother' of the Forum, designed for installations where severe or prolonged attack may occur. Angled body in zinc coated steel.

3mm opal polycarbonate diffuser secured by anti-tamper fixings.

620mm version is provided utilising a flat opal polycarbonate panel.

2250, 2450 & 2900lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".

4500, 4900 & 5800lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Textured Black
<b>IP:</b>	65
<b>IK:</b>	18

PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
TAB45/2/2250	2250	620mm	14W
TAB45/2/2450	2450	620mm	15W
TAB45/2/2900	2900	620mm	18W
TAB45/4/4500	4500	1200mm	28W
TAB45/4/4900	4900	1200mm	30W
TAB45/4/5800	5800	1200mm	35W

Other colours and technical modifications available, see page 29 for details.  
Anti-ligature as standard when ceiling mounted.


# TABOR COMPACT

## STRONG & DURABLE LED ANGLED LUMINAIRE

Designed for installations where severe or prolonged attack may occur.

400mm compact 60/30 degree angled body manufactured from zinc coated steel.

3mm opal polycarbonate flat panel secured by anti-tamper fixings.



### PRODUCT CODE

TAC60/4000

TAC60/6000

### LUMENS

4000

6000

### LOAD

25W

36W

### CCT:

4000K

### Finish:

Painted Textured Black


### IP:

65

### IK:

18





## TABOR SQUARE

### STRONG DURABLE LED RECESSED LUMINAIRE

Square recessed body manufactured from zinc coated steel with upstand recess.

Mounting through body sides to ceiling frame or through rear of body dependent on ceiling type.

3mm clear patterned polycarbonate flat panel secured by anti-tamper fixings.

**CCT:** 4000K  
**Finish:** Painted Textured Black  
**IP:** 65 from below  
**IK:** 16

PRODUCT CODE	LUMENS	LOAD
TAS/6500	6500	40W
TAS/8000	8000	51W

Other colours and technical modifications available, see page 29 for details.

# VARBERG


## STRONG & DURABLE LED RECESSED LUMINAIRE

Recessed linear LED fitting, unique upstand recessing flange, suitable for new installations or retrofitting into existing cavities when Bergo, Bergen or Victor have been removed.

body in Zinc coated steel.  
3mm clear patterned polycarbonate flat panel diffuser secured by anti-tamper fixings.

2250 & 2450 lm are supplied set to ordered level but version for on-site switchable output is available – add suffix "ADJ".


4500 & 4900 lm are supplied set to ordered level but version for on-site switchable output is available – add suffix "ADJ".



PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
VAR/2/2250/4000	2250	687 (634)	14W
VAR/2/2450/4000	2450	687 (634)	15W
VAR/2/4500/4000	4500	687 (634)	28W
VAR/2/4900/4000	4900	687 (634)	30W

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Textured Black
<b>IP:</b>	65
<b>IK:</b>	18

Other colours and technical modifications available, see page 29 for details.



**CCT:** 4000K  
**Finish:** Painted Textured White  
**IP:** 65  
**IK:** 14

PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
ARN/450/3000	3000	450mm	17W
ARN/600/6000	6000	600mm	36W
ARN/600/8000	8000	600mm	51W
ARN/750/8000	8000	750mm	51W
ARN/750/10000	10000	750mm	56W
ARN/900/12000	12000	900mm	70W

# ARENA

## GYMNASIUM AND GENERAL AREA LED LUMINAIRE

Designed for installation in gymnasiums / sports halls to protect against damage from ball games or accidental impact.

LED's offering high light output and maintenance free running, (tunable white available as an option in 600mm - 900mm diameter products).

Strong Circular aluminium spun body. 3mm clear polycarbonate diffuser with LED liner or Opal LED.

Available as 450mm, 600mm, 750mm & 900mm versions.

Technical modifications available, see page 29 for details.

# CITADEL

## SLIM-LINE CURVED PROFILE LED LUMINAIRE

Linear LED fitting with a slim-line curved profile capable of continuous mounting (available with optional cable trunking system).


Body in extruded aluminium. Machined aluminium end caps secured by anti-tamper fixings.

3mm opal polycarbonate control lens designed to achieve superior optical performance.

2250, 2450 & 2900lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".


4500, 4900 & 5800lm are supplied set to ordered level but version for on-site switchable output is available - add suffix "ADJ".

Other colours and technical modifications available, see page 29 for details.



PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
CIT/2/2250	2250	600mm	14W
CIT/2/2450	2450	600mm	15W
CIT/2/2900	2900	600mm	18W
CIT/4/4500	4500	1200mm	28W
CIT/4/4900	4900	1200mm	30W
CIT/4/5800	5800	1200mm	35W

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Smooth White
<b>IP:</b>	65
<b>IK:</b>	18



## CITADEL45

### ANGLED CURVED PROFILE LED LUMINAIRE

Angled LED fitting with a slim-line curved profile capable of continuous mounting (cable runs can be housed within angled back body).

Body in extruded aluminium, mounted on zinc coated steel angled bracket. Machined aluminium end caps secured by anti-tamper fixings.

3mm opal polycarbonate control lens designed to achieve superior optical performance.

2250, 2450 & 2900lm are supplied set to ordered level but version for on-site switchable output is available – add suffix “ADJ”.

4500, 4900 & 5800lm are supplied set to ordered level but version for on-site switchable output is available – add suffix “ADJ”.

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Smooth White
<b>IP:</b>	65
<b>IK:</b>	18

PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
CIT45/2/2250	2250	600mm	14W
CIT45/2/2450	2450	600mm	15W
CIT45/2/2900	2900	600mm	18W
CIT45/4/4500	4500	1200mm	28W
CIT45/4/4900	4900	1200mm	30W
CIT45/4/5800	5800	1200mm	35W

Other colours and technical modifications available, see page 29 for details.



# UPRAIL


## STRONG & DURABLE RAIL MOUNTED LINEAR LUMINAIRE

Stainless steel body and recessed diffuser and frame, painted in silver polyester powder coat (can also be provided in any RAL colour to match railing finish) c/w sloped top to eradicate anything being placed on top of the fitting (coffee cups or general litter).

Fits to the railing via a unique clamping system that eradicates the need to drill into either the railing itself or any support structure.

Opal or clear patterned polycarbonate diffuser secured by Torx pin security screws, bottom cable entry as standard.

Lumen outputs also available up to 6000 lumens dependent on final dimensions.




PRODUCT CODE	LUMENS	LENGTH	BW	FW	D
UPR/620/2000	2000	620	**	**	80*
UPR/620/2800	2800	620	**	**	60
UPR/1000/3000	3000	1000	**	**	60
UPR/1000/4000	4000	1000	**	**	60

\*Deeper to accommodate emergency gear option

\*\*Dimensions based on site railing sizes

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Silver
<b>IP:</b>	65
<b>IK:</b>	14



# ARCOLA

## CIRCULAR LED DOWNLIGHTER

Steel body and highly specular reflector

3mm opal polycarbonate panel housed within a die cast aluminium bezel secured by anti-tamper fixings.

Supplied with 500mm supply lead

Clear panel available— add suffix /CPP

Anti-Ligature version available—add suffix /AL

<b>CCT:</b>	4000K
<b>Finish:</b>	Painted Smooth White
<b>IP:</b>	65
<b>IK:</b>	16

PRODUCT CODE	LUMENS	LOAD
ARC/1150	1150	10W
ARC/1975	1975	17W
ARC/2900	2900	26W



Other colours and technical modifications available, see page 29 for details.

# BELLA


## ULTRA STRONG ARCHITECTURAL BOLLARD

A heavy duty bollard for areas that need something stronger, better and longer lasting.

Die cast aluminium bollard with cast iron anchor for solid in ground fixing. Available in either 360 degree symmetrical output or 2 way directional output.

1100mm high as standard but other heights available upon request.


Various lumen outputs available.



PRODUCT CODE	HEIGHT*	OUTPUT
BEL/SYM/1100/4000	1100	SYMMETRICAL
BEL/2WD/1100/4000	1100	2 WAY

\*Above ground.

<b>CCT:</b>	4000K
<b>Finish:</b>	RAL9005 Black
<b>IP:</b>	65
<b>IK:</b>	14



# ISLA

## ULTRA STRONG STAINLESS STEEL ARCHITECTURAL BOLLARD

A heavy duty bollard for areas that need something stronger, better and longer lasting.

Stainless steel bollard with anchor for solid in ground fixing.

360 degree symmetrical output.  
Available in either brushed finish or polished.

1100mm high as standard but other heights available upon request.

Various lumen outputs available.

**CCT:** 4000K  
**Finish:** Brushed or  
Polished Stainless Steel  
**IP:** 55  
**IK:** 08

PRODUCT CODE	HEIGHT*	FINISH
ISL/BRU/1100/4000	1100	BRUSHED
ISL/POL/1100/4000	1100	POLISHED

\*Above ground.



# MODIFICATION OPTIONS

All of our fittings can be modified to suit your project specific needs. The table below shows the most common modifications available. This list is not exhaustive so if you have a particular need, and it is not listed below, then please contact us.

DESCRIPTION	Add suffix	DESCRIPTION	Add suffix
SEMI-RECESSED	/SR	MICROWAVE SENSOR	/MIW
3 HOUR EMERGENCY	/EM3	SKI-SLOPE BODY	/SKI
CORRIDOR OPERATION	/COR	STAINLESS STEEL	/SS
DALI DIMMING	/DALI	CABLE TRUNKING SYSTEM	/CMS
1-10V DIMMING	/10VD	ANTI-LIGATURE VERSION	/AL
CCT: 3000K	/3000	PAINTED TEXTURED WHITE (RAL 9016)*	/W
PHOTOCELL	/PEC	END CONDUIT ENTRY	/ECE
SEPARATE CIRCUITS	/SEC	SWITCH DIM	/SWD
NIGHT LIGHT	/NIL		



**ELEMENTS**   
BY AETHER LIGHTING

Affordable  
and Reliable  
Interior Lighting





**WASH**  
Page 34



**LINER**  
Page 35



**RING**  
Page 36



**DISC**  
Page 37



**ARCOLA 85**  
Page 38



**ARCOLA 195**  
Page 39



**ROTUNDA**  
Page 40



**GLANCE**  
Page 41



**SHALLOW MINI**  
Page 42



**SHALLOW**  
Page 43



**GRID**  
Page 44



**GRID WING**  
Page 45



**VAP**  
Page 46





**BATT**  
Page 47

# WASH

## LED WALL LUMINAIRE

A decorative wall mounted LED luminaire with bidirectional light output and opal diffusers for homogeneous illumination.





PRODUCT CODE	LUMENS	LOAD
WASH/9/4000K	825	9W
WASH/16/4000K	1500	16W
WASH/24/4000K	2250	24W

**Dims:** 400mm x 110mm x 81mm

**Mounting:** Wall mounted. Vertical or horizontal mounting

**Control Gear:** Various dimming options available. /DIM

**Finish:** White or Black paint finish /W, /B.  
Other colours and specifications available on request.



# LINER

## LED WALL LUMINAIRE

A versatile linear LED luminaire with various options and accessories available.

Luminaire is available in surface mounted, suspended, or recessed versions and is suitable for use as a single luminaire or as a continuous system to provide various length runs.

LINER Luminaire is complete as standard with an opal TP(a) diffuser. A Low Glare prismatic diffuser option is available for office and LG7 compliance /LG.

- Dims:** Single lengths: 850mm/1200mm/1500mm. Various length continuous runs available.
- Mounting:** Surface mounted /SM. Suspended via wire suspensions /SUS. Recessed /REC
- Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM  
Available with 3 hour emergency /EM
- Finish:** White, Black or Grey paint finish /W, /B, /G.  
Other colours and specifications available on request.



PRODUCT CODE	LUMENS
LIN/850/4000K	1825
LIN/1200/4000K	2725
LIN/1500/4000K	3325

Other outputs, options and accessories available.

# RING

## LED RING PENDANT

A suspended LED ring luminaire with an opal acrylic diffuser.




PRODUCT CODE	LUMENS	LOAD
RING/47/4000K	2625	47W
RING/86/4000K	5025	86W

**Dims:** ø600mm x 105mm / ø1200mm x 105. Other diameters available on request.

**Mounting:** Suspended via adjustable wire suspensions

**Control Gear:** Various dimming options available. /DIM

**Finish:** White, Black or Grey paint finish /W, /B, /G.  
Other colours and specifications available on request.



# DISC

## LED DISC PENDANT

A suspended LED disc luminaire with an opal acrylic diffuser.

**Dims:** ø600mm x 105mm / ø1200mm x 105. Other diameters available on request.

**Mounting:** Suspended via adjustable wire suspensions.

**Control Gear:** Various dimming options available. /DIM

**Finish:** White, Black or Grey paint finish /W, /B, /G.  
Other colours and specifications available on request.


PRODUCT CODE	LUMENS	LOAD
DISC/54/4000K	4775	54W
DISC/137/4000K	15700	137W

Other outputs, options and accessories available.

# ARCOLA 85

## MINI IP65 LED DOWNLIGHT

A recessed fire rated FR90, IP65 mini LED downlight luminaire suitable for a wide range of applications.




PRODUCT CODE	LUMENS	LOAD
ARC85/8/4000K	775	8W

**Dims:** 85mm x 60mm

**Mounting:** Ceiling recessed. Supplied with IP ceiling gasket

**Control Gear:** Remote Tridonic or Philips driver.  
Various dimming options available. /DIM. Available with 3 hour emergency /EM.  
Casambi Bluetooth wireless network (inc dim) option available /BTC

**Finish:** White, Black and Brushed bezel finish options available /W, /B, /BRS



**Dims:** 195mm x 112/132mm

**Mounting:** Ceiling recessed

**Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM. Available with 3 hour emergency/EM. Casambi Bluetooth wireless network (inc dim) option available /BTC

**Finish:** Various bezel and finish options available including – Drop halo, Snoot, IP65, IP54 glass and Hi-light options

# ARCOLA 195

## LED DOWNLIGHT

A high-performance recessed LED downlight luminaire suitable for a wide range of applications with a die-cast twist and lock bezel feature for interchangeable accessories, including decorative and IP rated bezel options.

PRODUCT CODE	LUMENS	LOAD
ARC195/9.5/4000K	1100	9.5W
ARC195/17.5/4000K	1900	17.5W
ARC195/30.5/4000K	2925	30.5W
ARC195/46.5/4000K	4550	46.5W


Available in - /3000K & /4000K.  
Various options and accessories available.



# ROTUNDA

## LED DOWNLIGHT

A recessed LED downlight luminaire suitable for a wide range of applications with a range of options and accessories including decorative and IP65 bezel options.




PRODUCT CODE	LUMENS	LOAD
ROT/8/4000K	1075	8W
ROT/14/4000K	1800	14W
ROT/19/4000K	2450	19W
ROT/28/4000K	3275	28W

**Dims:** 130mm x 99mm

**Mounting:** Ceiling recessed. Plaster in option available. /PI

**Control Gear:** Remote Tridonic or Philips driver. Various dimming options available. /DIM. Available with 3 hour emergency /EM. Casambi Bluetooth wireless network (inc dim) option available /BTC

**Finish:** Bezel and finish options available including – Drop halo, Snoot, IP65, IP54 glass and Hi-light options



# GLANCE

## LED WALL LUMINAIRE FOR STAIRWAYS

A stairway LED wall luminaire with a unique LED gear tray arrangement for stairway applications - providing directional light onto stair treads whilst maintaining a uniform illuminated appearance. Luminaire complete with polycarbonate body and diffuser.

**Dims:** 430mm x 111mm

**Mounting:** Wall mounted

**Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM.  
Available with 3 hour emergency /EM

**Finish:** White finish as standard. Other colours and various decorative trim options available /TRIM. Halo effect versions available /HALO

PRODUCT CODE

GLA/19/4000K

LUMENS

1800


LOAD

19W

# SHALLOW MINI

## LED DOWNLIGHT

A shallow depth recessed mini commercial LED downlight luminaire with an opal polycarbonate diffuser and RAL9016 bezel. IP54 as standard.




PRODUCT CODE	LUMENS	LOAD
SHAM/9/4000K	850	9W

**Dims:** 110mm x 46mm

**Mounting:** Ceiling recessed

**Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM.  
Available with 3 hour emergency /EM. Casambi Bluetooth wireless network (inc dim)  
option available /BTC

**Finish:** RAL9016 bezel



# SHALLOW

## LED DOWNLIGHT

A shallow depth recessed commercial LED downlight luminaire with an opal polycarbonate diffuser and RAL9016 bezel. IP54 as standard.

**Dims:** 190mm x 46mm

**Mounting:** Ceiling recessed

**Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM. Available with 3 hour emergency /EM. Casambi Bluetooth wireless network (inc dim) option available /BTC

**Finish:** RAL9016 bezel


PRODUCT CODE	LUMENS	LOAD
SHA/11/4000K	1200	11W
SHA/21/4000K	2275	21W

Switchable 3 x CCT - 3000K, 4000K, 5500K

# GRID

## LED PANEL

An ultra slim depth 600 x 600 lay-in LED panel. Low Glare UGR <19 for LG7 compliance. Part L and ETL compliant efficacies. Self-extinguishing TP(a) diffuser option available /TPA.



PRODUCT CODE	LUMENS	LOAD
GRD/26/4000K	3100	26W
GRD/34.5/4000K	3900	34.5W


**Dims:** 596mm x 595mm x 8.5mm

**Mounting:** Lay-in ceiling recessed. Plasterboard mounting kit option available /PMK. Suspension Kit option available /SUS. Surface mount frame option available /SM

**Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM. Available with 3 hour emergency /EM. Casambi Bluetooth wireless network (inc dim) option available /BTC

**Finish:** White finish

Available in - /3000K & /4000K.  
Other outputs, options and accessories available.



# GRID WING

## LED MODULAR

A 600 x 600 LED modular with micro prismatic central diffuser which is packed with features and options to provide a safe and comfortable working environment.

**Dims:** 593mm x 589mm x 100mm

**Mounting:** Ceiling recessed. Plasterboard mounting kit option available /PMK.  
Suspension Kit option available /SUS. Surface mount frame option available /SM

**Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM.  
Available with 3 hour emergency /EM. Casambi Bluetooth wireless network (inc dim) option available /BTC

**Finish:** White finish

PRODUCT CODE	LUMENS	LOAD
GRDW/31.5/4000K	3200	31.5W
GRDW/32/4000K	3575	32W
GRDW/46/4000K	5125	46W
GRDW/52/TW	3875	52W

Available in - /3000K & /4000K  
and 3000K– 6000K Tunable white /TW.  
Other outputs, options and accessories available.

# VAP

## IP65 LED BATTEN LUMINAIRE

IP65 anti-corrosive LED batten with a robust injection moulded polycarbonate body.

Luminaire fitted with an opal light pipe for homogeneous output and a clear vapour proof, high impact diffuser. Quick release flush mounted fixing clips. IK10.



PRODUCT CODE	LUMENS	LENGTH (L)	LOAD
VAP/19/4000K	2900	1500mm	19W
VAP/36/4000K	5500	1500mm	36W


**Dims:** W: 104mm D: 80mm L: 1500mm

**Mounting:** Surface mounted. Corner mounting kit /CMK 1.5m suspension kit /SUS

**Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM.  
Available with 3 hour emergency /EM

**Finish:** Grey. Stainless steel clips available /SSC

Available in - /3000K & /4000K  
Other outputs, options and accessories available.



# BATT

## LED BATTEN

A LED batten with an aluminium body and integral gear tray complete with opal diffuser.

**Dims:** W: 55mm D: 60mm L: 1200mm

**Mounting:** Surface mounted

**Control Gear:** Tridonic or Philips driver. Various dimming options available. /DIM.  
Available with 3 hour emergency /EM

**Finish:** White Paint finish.

PRODUCT CODE	LUMENS	LOAD
BAT/26/4000K	3300	26.6W





**ONE2SEE SIGNS**   
BY AETHER LIGHTING

## **SIGNS**

INTERNALLY ILLUMINATED ROAD SIGNS

## **TRAYS**

LED RETRO-FIT GEAR TRAYS

## **BOLLARDS**

LED INTERNALLY LIT BOLLARDS

## SIGNS

# COSMO

LED INTERNALLY  
ILLUMINATED ROAD SIGN

**SLIM-BODIED - 75MM**

Low energy and slimline


Option to house customer  
CMS module upon request.



RANGE / SHAPE SIZE (mm) / COLOUR / TSRGD GRAPHIC CODE

### Circles

COS	/	C	300	/	G (Grey)	/	***
			450		B (Black)		
			600				
			750				
			900				
			1200				



### Triangles

COS	/	T	600	/	G (Grey)	/	***
			750		B (Black)		
			900				



### Rectangles

COS	/	R	300 x 450	/	G (Grey)	/	***
					B (Black)		



Optional Extra's (Add bold code as suffix to above):

**P76** - Post Top Bracket to fit a 76mm column

**P89** - Post Top Bracket to fit a 89mm column


**SOL** - Solar Power (supplied without the column as kit)

**SOL4** - Solar Power (supplied as standard with a 4m lighting column)

**12V** - 12vDC Supply (standard version wired for 240v - incoming voltage)

**24V** - 24vDC Supply (standard version wired for 240v - incoming voltage)

Example Code: **COS/C600/B/606**



RANGE / SHAPE SIZE (mm) / COLOUR / TSRGD GRAPHIC CODE

### Circles

MET	/	C	SIZE (mm)	/	COLOUR	/	TSRGD GRAPHIC CODE
			300	/	G (Grey)	/	***
			450		B (Black)		
			600				
			750				
			900				
			1200				

### Triangles

MET	/	T	SIZE (mm)	/	COLOUR	/	TSRGD GRAPHIC CODE
			600	/	G (Grey)	/	***
			750		B (Black)		
			900				

### Rectangles

MET	/	R	SIZE (mm)	/	COLOUR	/	TSRGD GRAPHIC CODE
			300 x 450	/	G (Grey)	/	***
					B (Black)		

Optional Extra's (Add bold code as suffix to above):

**P76** - Post Top Bracket to fit a 76mm column

**P89** - Post Top Bracket to fit a 89mm column

**SOL** - Solar Power (supplied without the column as kit)

**SOL4** - Solar Power (supplied as standard with a 4m lighting column)

**12V** - 12VDC Supply (standard version wired for 240v - incoming voltage)

**24V** - 24VDC Supply (standard version wired for 240v - incoming voltage)

Example Code: **MET/C750/G/616**

## SIGNS

# METRO

LED INTERNALLY  
ILLUMINATED ROAD SIGN

**DEEPER-BODIED - 100mm**

Low energy and deeper bodies to  
house a NEMA socket.



## TRAYS

# LED RETRO-FIT GEAR TRAYS


For all illuminated road signs

Save energy by replacing all your old fluorescent Type A & internally illuminated signs with a One2See retro-fit LED gear tray.

**In many cases NO re-wiring required, simply "UNPLUG THE OLD AND PLUG IN THE NEW", in less than a minute!**

Whatever make or model you have, we have designed and manufactured a tray to fit it - we think you'll love them. In fact we love them so much we gave them all names and created our own retro-fit family!

## Meet some of our retro-fit family




**The following are our most popular retro-fit gear trays:**

### FITTING TYPE

### SPECIFICATION CODE

Simmons Type 'A'	SIMON*
Forest City 'A' Type	EMMA
Simmons Invinca	SAYA
Mallatite Titan 'A' Type	SID
Mallatite Delta 'A' Type	MANI
Zetec 'A' Type	CHIN

\*See opposite page

**PRODUCT CODE**

SIMON/5W/4000

**LOAD**

5W

**CCT:**

4000K

**Finish:**

White

**TRAYS****SIMON****SIMMONS LUA TYPE A LED  
RETRO-FIT GEAR TRAY**

Gear tray/reflector to suit Simmons  
LUA Type A housing c/w all  
components including 70 lux photocell.

Simple installation by removing all  
existing internal tray and components,  
fit new white powder coated steel gear  
tray, now connect via the supplied plug  
and socket which matches the existing  
coupler within the installed product.

**NO wiring required, simply "UNPLUG  
OLD AND PLUG IN NEW".**

Comes with a 5 year warranty.

## BOLLARDS

# BOROUGH

LED INTERNALLY  
ILLUMINATED ROAD BOLLARD

### 50MM DIAMETER

Strong and durable slimline bollard.


W: 450mm  
H: 1000mm  
D: 50mm



Illuminated sign operates on 24vDC but bollard is supplied based on project incoming voltage.

Available in mild steel (painted black or grey) or stainless steel (painted black or grey or brushed).

Available with a choice of fixing methods: flange feet, flange plate, in ground box or NAL sockets.



RANGE	/	GRAPHIC SIZE (mm)	COLOUR	/	INCOMING VOLTAGE	FIXING DETAIL	/	TSRGD CODE
BBOL	/	300	G (Grey Mild Steel)	/	12V (12vDC)	FF (Flange Feet [Round])	/	***
			B (Black Mild Steel)		24V (24vDC)	FP (Flange Plate)		
			SS (Brushed SS)		240 (240v)	NAL (NAL socket*)		
			SSB (Black SS)			IG (in ground box**)		
			SSG (Grey SS)					

**Optional Extra's** (Add bold code as suffix to above):

**BTB** - back to back version with illuminated sign on both sides


**NIL** - Non-illuminated

\*Bollard supplied with longer legs (NAL sockets not supplied)

\*\*Other in ground options available by request.

Example Code: **BBOL/300G/240FF/606**





Illuminated sign operates on 24vDC but bollard is supplied based on project incoming voltage.

Available in mild steel (painted black or grey) or stainless steel (painted black or grey or brushed).

Available with a choice of fixing methods: flange feet, flange plate, in ground box or NAL sockets.

RANGE	/	GRAPHIC SIZE (mm)	COLOUR	/	INCOMING VOLTAGE	FIXING DETAIL	/	TSRGD CODE
CBOL	/	300	G (Grey Mild Steel)	/	12V (12vDC)	FF (Flange Feet [Round])	/	***
			B (Black Mild Steel)		24V (24vDC)	FP (Flange Plate)		
			SS (Brushed SS)		240 (240v)	NAL (NAL socket*)		
			SSB (Black SS)			IG (in ground box**)		
			SSG (Grey SS)					

**Optional Extra's** (Add bold code as suffix to above):

**BTB** - back to back version with illuminated sign on both sides

**NIL** - Non-illuminated

\*Bollard supplied with longer legs (NAL sockets not supplied)

\*\*Other in ground options available by request.

Example Code: **CBOL/300B/24VFP/610**

## BOLLARDS

### CITY

#### LED INTERNALLY ILLUMINATED BOLLARD

**76MM DIAMETER**  
Ultra-strong bollard.

W: 570mm

H: 1025mm

D: 76mm





Our LED retro-fit trays are designed, manufactured and assembled in the UK and will be easy to fit into your existing lighting with, in most cases, no re-wiring required.




**RETRO-FIT**   
BY AETHER LIGHTING

High quality,  
efficient and easy  
to fit retro-fit  
gear trays for  
commercial  
premises

Most buildings were designed with good quality lighting at the initial stage and there is no reason to replace existing inefficient fluorescent trays with cheap, short lived, inefficient LED's.

Instead, update with our retro-fit trays which come with a long life 5 year warranty using Tridonic or Philips LED's and drivers to establish and achieve low maintenance, high quality lighting with short term payback periods, often under a year based on current electrical costs!



# RETRO-FIT

---



Manufactured in the UK in our own factory and designed to suit all environments:

- PRISONS
- RAILWAYS
- TRANSPORT
- SECURE AND GENERAL HOSPITALS
- DEMENTIA AND MENTAL HEALTH UNITS
- COMMERCIAL OFFICES
- COMMERCIAL BUILDINGS

All our trays are designed to be specific to the customers requirements with lighting levels calculated to achieve current lighting and emergency levels.

We will be happy to visit your premises to evaluate your needs, following up with a detailed survey and offer a lighting design and quotation free of charge.

Call us to arrange an appointment for your  
**FREE** survey and quotation.




**MADE2SPEC**  
BY AETHER LIGHTING 

Manufacturing  
bespoke light  
fittings to  
your design  
specifications.



Our Made2Spec range puts our full manufacturing facility at your disposal allowing us to manufacture bespoke light fittings to your specification.

This partnership of your design and our manufacturing has led us to be involved in some very exciting and rewarding projects including The Royal Albert Hall, Guildhall, The National Theatre and the V&A.





## PREVIOUS PROJECTS INCLUDE:

HEINEKEN GREEN ROOM  
CLISSOLD HOUSE  
EBURY SQUARE  
GLASGOW SCHOOL OF ART  
GUILDHALL  
ROYAL ALBERT HALL  
SALFORD MEDIA CITY  
SHERBORNE ABBEY  
THE NATIONAL THEATRE

Contact us for more information:

**e: [info@made2spec.co.uk](mailto:info@made2spec.co.uk)**  
**t: 020 8254 0095**





[www.aetherlighting.com](http://www.aetherlighting.com)

t: 020 8254 0094 | e: [info@aetherlighting.com](mailto:info@aetherlighting.com)

INCORPORATING:

ENDURANCE

ELEMENTS

ONE2SEE SIGNS

RETRO-FIT

MADE2SPEC