ELEMENTS - LINER

AETHER LINER Linear LED luminaire

SPECIFICATION

AETHER REFERENCE: LIN

DESCRIPTION AND HOUSING	A versatile linear LED luminaire with various options and accessories available. Luminaire is available in surface mounted, suspended, or recessed versions and is suitable for use as a single luminaire or as a continuous system to provide various length runs. LINER Luminaire is complete as standard with an opal TP(a) diffuser. A Low Glare prismatic diffuser option is available for office and LG7 compliance /LG
LENGTHS	Single lengths: 850mm/1200mm/1500mm. Various length continuous runs available. <i>Please</i>
AVAILABLE	enquire.
LIGHT SOURCE	Luminaires are available with various output options - Standard output, Low output and High output. The below data is for standard output 4000K. For other output options <i>Please enquire</i> . For Surface mounting add suffix /SM. For Suspended add suffix /SUS. For Recessed add suffix /REC Length 850mm - 1825 Lumen LED REF: LIN/850/4000K Length 1200mm - 2725 Lumen LED REF: LIN/1200/4000K Length 1500mm - 3325 Lumen LED REF: LIN/1500/4000K Available in - /3000K & /4000K Please note: Other outputs, options, and accessories available.
MOUNTING	Surface mounted /SM. Suspended via wire suspensions /SUS. Recessed /REC
CONTROL GEAR	Tridonic driver. Various dimming options available. /DIM. Available with 3 hour emergency /EM.

Data Sheet

Liner LINEAR LED LUMINAIRE



White, Black or Grey paint finish /W, /B, /G. *Please note: Other colours and specifications available on request.*

Data Sheet







